



#### 規格表

示意圖	規格	負荷重量 (kgs)	負荷 kg/cm <sup>2</sup>	示意圖	規格	負荷重量 (kgs)	負荷 kg/cm <sup>2</sup>	
	YS-480x240x25P	2304~5760	2 - 5		YS-315x315x13P	1984~4961	2 - 5	
	YS-240x240x25P	1152~2880	2 - 5		YS-315x156x13P	983~2457	2 - 5	
	YS-50x50x25P	50~125	2 - 5		YS-100x100x25P	200~500	2 - 5	
	YS-50x50x50P	50~125	2 - 5		YS-150x150x50P	450~1125	2 - 5	
	YS-197x197x17P	1940~3492	5 - 9			YS-345x345x9P	2380~5951	2 - 5
	YS-350x74x17P	1295~2331	5 - 9			YS-176x176x9P	620~1548	2 - 5
	YS-226x74x17P	836~1505	5 - 9	YS-390x390x3.2P		6084~9126	4 - 6	
	YS-120x120x17P	720~1296	5 - 9	YS-320x320x3.2P		4096~6144	4 - 6	
				YS-260x260x3.2P		2074~4056	4 - 6	

#### 特性

- ◎ 裝置簡便、固定性佳。
- ◎ 採用丁基橡膠 (Butyl Rubber)，防振效果佳。
- ◎ 表面採用溝梯形設計，正反兩面相互垂直，增加防振效果。
- ◎ 適用於冷卻水塔、馬達空調機等空調設備。
- ◎ 墊片尺寸可依實際需要做裁切。



水平管安裝YS-P橡膠墊片



立式水泵安裝YS-P橡膠墊片