


Air Springs For Commerical Vehicles

PERFECTION / INNOVATION / IMAGINATION

» Order NO :YS-D11232 / 1



TOP VIEW



BOTTOM VIEW



Static Data

Load H mm	Inner Pressure kg/cm ²				
	2	3	4	5	6
min 120	149	212	292	376	472
140	135	192	287	363	466
160	135	217	294	374	461
180	128	194	288	367	464
200	123	200	295	377	480
max 210	132	217	314	406	484

max.Diameter : 129ø

» Order NO :YS-D11232 / 2



TOP VIEW



BOTTOM VIEW

- M50XP1.5
- M50XP2.0
- M52XP1.5
- M52XP2.0

Static Data

Load H mm	Inner Pressure kg/cm ²				
	2	3	4	5	6
min 138	149	212	292	376	472
158	135	192	287	363	466
178	135	217	294	374	461
198	128	194	288	367	464
218	123	200	295	377	480
max 228	132	217	314	406	500

max.Diameter : 129ø

» Order NO :YS-120VC



TOP VIEW



BOTTOM VIEW

- M50XP1.5
- M50XP2.0
- M52XP1.5
- M52XP2.0

Static Data

Load H mm	Inner Pressure kg/cm ²				
	2	3	4	5	6
min 138	211	246	350	403	467
148	184	241	297	369	425
168	94	145	186	235	281
max 178	47	85	126	162	200

max.Diameter : 123ø

